

XIAMEN JOINT TECH. CO., LTD.

JOINT TECH, BORN FOR SUSTAINABLE ENERGY

🌐 <https://jointcharger.com>

✉ info@jointcharger.com

📍 No. 98, South Dongfu Road, Haicang District, Xiamen, China

EVD100 / DCFC

60/120/180KW



DURABILITY

NEMA 3R and IK10 protection ratings, allowing for indoors or outdoors.



ISO15118 & DIN70121

(Plug&Charge) enhances customer experience.



CONNECTED

Complete with LTE & Wi-Fi & Ethernet connectivity, ensuring chargers are always online.



INTERACTION

10 inch touch screen with user friendly interface.




OCPP

OCPP 1.6J help you connect EV charger to the cloud.



COMPATIBLE

CCS type 1 plug with 13ft cable.



Color:  

DATASHEET

Model No.		EVD100/60U	EVD100/120U	EVD100/180U
AC Input	Number of Phase / Wire	3ph/L1, L2, L3, N, PE		
	Voltage	480Vac(+10%, -15%)		
	AC Input Power @ 480V 60Hz	77A, 64kVA	155A, 128kVA	235A, 192kVA
	Frequency	50/60Hz		
	Power factor	PF≥0.98@Rated load		
	Efficiency	>94%		
DC Output	Maximum Power	60KW	120KW	180KW
	Voltage Operating Range	200-1000V		
	Cable Maximum Current	200A	250A	250A
	Charging Outlet	CCS1 with 13ft cable		
Display		10 inch touch screen		
User Authentication		Plug & Play /RFID /QR Code		
EV Communication		ISO15118 & DIN70121		
Network		Ethernet, LTE, Wi-Fi		
Connectivity		OCPP1.6J		
Operating Temperature		-22°F to 122°F		
IP Level		NEMA 3R		
Cooling		Forced Air		
Operating noise level		≤65dB		
Altitude		≤6561ft		
Product Dimensions		18.9" (D) x 27.6" (W) x 67.5" (H)		
Package Dimensions		/		

OCPP 1.6J

Connected successfully with 50+ global EVC platforms



DIMENSIONS

