



EVC10 / Mode 3

UP TO 22KW

CE CB UK CA TR25



3 years limited warranty

DURABILITY

IP65 and IK08 protection ratings, allowing for indoors or outdoors.



POWERFUL

Up to 22kW of charging capacity.



CONNECTED

Complete with LAN connectivity (Wi-Fi or 4G optional), ensuring chargers are always online.



CONVENIENT

Adjust power as needed, 32A-16A.



OCPP

OCPP 1.6J help you connect EV charger to the cloud.



COMPATIBLE

IEC 62196 compliant, type 2 plug with 5m cable.



Color:  

DATASHEET

Model No.	EVC10/AC07	EVC10/AC11	EVC10/AC22
Voltage	230Vac±10%	400Vac±10%	
Amperage/Power	32A/7KW	16A/11KW	32A/22KW
AC Power Frequency	50-60Hz		
Display	4.3" LCD		
User Authentication	RFID ISO14443		
Network	Ethernet, Wi-Fi or 4G optional		
Connectivity	OCPP1.6J		
Operating Temperature	-30°C ~ 50°C		
IP Level	IP65/IP54(socket)		
IK Rating	IK08		
Cable Length	5 meters (7 meters optional)		
Net Weight	5.2kg (C) / 3.7kg (S)	4.9kg (C) / 3.9kg (S)	6.5kg (C) / 3.9kg (S)
Gross Weight	6.3kg (C) / 4.7kg (S)	6.0kg (C) / 4.9kg (S)	7.6kg (C) / 4.9kg (S)
Product Dimensions	351 x 250 x 130mm (Cable) / 351 x 250 x 155mm (Socket)		
Package Dimensions	497 x 348 x 272mm (Cable) / 444 x 324 x 215mm (Socket)		

OCPP 1.6J

Connected successfully with 50+ global EVC platforms



DIMENSIONS



Package Dimensions
497x348x272mm



Package Dimensions
444x324x215mm