

# XIAMEN JOINT TECH. CO., LTD.

JOINT TECH, BORN FOR SUSTAINABLE ENERGY

🌐 [www.jointcharging.com](http://www.jointcharging.com)

✉ [info@jointcharging.com](mailto:info@jointcharging.com)

📍 No.98, South Dongfu Road, Haicang District, Xiamen, China

# EVD001

20/30/40KW



2 years limited warranty



## MAINTAIN

Pull-out power module



## DIN 70121

(Plug&Charge) enhances customer experience.



## CONNECTED

Complete with LTE & Wi-Fi & Ethernet connectivity, ensuring chargers are always online.



## INTERACTION

7 inch touch screen with user friendly interface.




## OCPP

OCPP 1.6J help you connect EV charger to the cloud.



## TWO GUNS

Charge 2 vehicles simultaneously



# Ocpp 1.6J

Connected successfully with 50+ global EVC platforms



# DATASHEET

Model No.		JNT-EVD001/020	JNT-EVD001/030	JNT-EVD001/040
AC Input	Number of Phase / Wire	3ph/L1, L2, L3, N, PE		
	Voltage Rating	400 Vac ±10%		
	Max. Input Amperage	35A	50A	70A
	Frequency	50~60Hz		
	Power factor	PF≥0.99@Rated load		
	Efficiency	> 95%		
DC Output	Maximum Power	20KW	30KW	2*20KW
	Voltage Operating Range	CCS2: 150-920 Vdc		CHAdeMO: 150-500 Vdc
	Maximum Current	60A	80A	2*60A
	Plug Type	1*CCS2		2*CCS2 or 1*CCS2+1*CHAdeMO
	Charger gun length	4m Standard; 5m Optional		
<b>Function</b>				
EV Communication		DIN 70121		
User Authentication		Plug&Play / RFID / QR Code		
Display		7 inch touch screen		
Network		Ethernet, 4G, Wi-Fi		
Connectivity		OCPP 1.6 J		
Languages		English as standard Others languages available via software configuration		
<b>Protection</b>				
Certificate		CE		
Safety Compliance		IEC 61851-1, IEC 61851-21-2, IEC 61851-23, IEC 61851-24		
Multiple Protection		Overcurrent protection, Short circuit protection, Input / Output Overvoltage protection, Input Undervoltage protection, Insulation monitoring, Two DC connector output common ground protection, Reverse polarity protection, Over temperature protection		
Warranty		2 year		
<b>Environmental</b>				
Storage Temperature		-40°C to 75°C		
Operating Temperature		-20°C to 55°C		
Anti-vandalism		IK10 (not include LCD & RFID cover)		
Ingression		IP54		
Relative Humidity		Up to 95% non-condensing		
Cooling		Forced Air		
Operating noise level		≤ 65dB		
Altitude		≤ 2000M		
<b>Mechanical Feature</b>				
Dimension (mm)		460 (W) *670 (H) *270 (D)		
Charger Weight (without Packing)		35kg	40kg	65kg
Input cable and connection		Not included		
Mounting		Wall or floor using a pedestal		

# DIMENSIONS

